

Recommended spacing requirement from top of installation plate to the ceiling  
各款分體機背板與天花最少安裝距離的建議

Product Line 產品系列	Model 型號	Type 類型	A Min. Height for Right rear piping (mm) 喉管安裝在右時最少相距(毫米)	B Min. Height for Left rear piping (mm) 喉管安裝在左時最少相距(毫米)
PAH	MSZ-PAH09VA-H1/ MUZ-AH09VA-H1	Inverter Heat pump	95	185
	MSZ-PAH12VA-H1/ MUZ-AH12VA-H1			
WG	MSZ-WG18VA-H1/ MUZ-WG18VA-H1		82	123
	MSZ-WG20VA-H1/ MUZ-WG20VA-H1			
	MSZ-WG25VA-H1/ MUZ-WG25VA-H1			
YK	MSZ-YK09VA-H1/ MUZ-YK09VA-H1		65	161
	MSZ-YK12VA-H1/ MUZ-YK12VA-H1			
	MSZ-YK18VA-H1/ MUZ-YK18VA-H1			
GE	MSZ-GE60VA-E1/ MUZ-GE60VA-E1		55	118
	MSZ-GE71VA-E1/ MUZ-GE71VA-E1			
GS	MSZ-GS07VF/ MUZ-GS07VF	55	130	
	MSZ-GS09VF/ MUZ-GS09VF			
	MSZ-GS12VF/ MUZ-GS12VF			
	MSZ-GS18VF/ MUZ-GS18VF			
LN	MSZ-LN09VFR/V/B/ MUZ-LN09VF	60	150	
	MSZ-LN12VFR/V/B/ MUZ-LN12VF			
	MSZ-LN18VFR/V/B/ MUZ-LN18VF			
MSY	MSY-GJ10VA MUY-GJ10VA	Inverter Cooling only	56	125
	MSY-GJ13VA MUY-GJ13VA			
	MSY-GK18VA MUY-GK18VA		55	118
	MSY-GF24VA MUY-GF24VA			
GS	MSY-GS07/ MUY-GS07	55	130	
	MSY-GS09/ MUY-GS09			
	MSY-GS12/ MUY-GS12			
	MSY-GS18/ MUY-GS18			
GJ	MS-GJ09VA MU-GJ09VA	Fixed speed Cooling only	54	130
	MS-GJ12VA MU-GJ12VA			
GM/GH	MS-GM19VA MU-GM19VA	55	118	
	MS-GM23VA MU-GM23VA			
	MS-GH80VA MU-GH80VA			