

Recommended spacing requirement from top of installation plate to the ceiling
各款分體機背板與天花最少安裝距離的建議

Product Line 產品系列	Model 型號	Type 類型	A Min. Height for Right rear piping (mm) 喉管安裝在右時最少相距(毫米)	B Min. Height for Left rear piping (mm) 喉管安裝在左時最少相距(毫米)	
YK	MSZ-YK09VA-H1/ MUZ-YK09VA-H1		65	161	
	MSZ-YK12VA-H1/ MUZ-YK12VA-H1				
	MSZ-YK18VA-H1/ MUZ-YK18VA-H1				
GE	MSZ-GE60VA-E1/ MUZ-GE60VA-E1		55	118	
	MSZ-GE71VA-E1/ MUZ-GE71VA-E1				
GS	MSZ-GS07/ MUZ-GS07		55	130	
	MSZ-GS09/ MUZ-GS09				
	MSZ-GS12/ MUZ-GS12			132	
	MSZ-GS18/ MUZ-GS18				
LN	MSZ-LN09VFR/V/B/ MUZ-LN09VF		60	150	
	MSZ-LN12VFR/V/B/ MUZ-LN12VF				
	MSZ-LN18VFR/V/B/ MUZ-LN18VF				
	MSZ-LN22VFR/V/B/ MUZ-LN22VF				
MSY	MSY-GJ10VA MUY-GJ10VA	Inverter Cooling only	56	125	
	MSY-GJ13VA MUY-GJ13VA				
	MSY-GK18VA MUY-GK18VA		55	118	
	MSY-GF24VA MUY-GF24VA				
GS	MSY-GS07/ MUY-GS07		55	130	
	MSY-GS09/ MUY-GS09				
	MSY-GS12/ MUY-GS12			132	
	MSY-GS18/ MUY-GS18				
GJ	MS-GJ09VA MU-GJ09VA		Fixed speed Cooling only	54	130
	MS-GJ12VA MU-GJ12VA				
GM/GH	MS-GM19VA MU-GM19VA	Fixed speed Cooling only	55	118	
	MS-GM23VA MU-GM23VA				
	MS-GH80VA MU-GH80VA				